
plug socket with cable NEBV-HSG2-KN-1-N-LE2 Part number: 566663









Data sheet

| Feature | Value | |
|------------------------------------------------|----------------------------------|--|
| Cable identification | Without inscription label holder | |
| Assembly position | Any | |
| Product weight | 7 g | |
| Electrical connection 1, function | Field device side | |
| Electrical connection 1, design | Angular | |
| Electrical connection 1, connection type | Plug socket | |
| Electrical connection 1, cable outlet | Straight | |
| Electrical connection 1, connection technology | Connection pattern S | |
| Electrical connection 1, number of pins/wires | 2 | |
| Electrical connection 1, occupied pins/wires | 2 | |
| Electrical connection 1, type of mounting | Snap-in locking | |
| Electrical connection 2, function | Controller side | |
| Electrical connection 2, connection type | 2 single wires | |
| Electrical connection 2, connection technology | Open end | |
| Electrical connection 2, number of pins/wires | 2 | |
| Electrical connection 2, occupied pins/wires | 2 | |
| Operating voltage range DC | 0 60 V | |
| Acceptable current load at 40°C | 3 A | |
| Cable length | 1 m | |
| Cable attribute | Standard | |
| Cable diameter | 1.3 mm | |
| Cable structure | 2x0,14 | |
| Nominal conductor cross-section | 0.14 mm2 | |
| Wire ends | Cut off bluntly | |
| Protection class | IP40 | |
| Note on degree of protection | in assembled condition | |
| Ambient temperature | -5 60 °C | |
| Materials note | Conforms to RoHS | |
| Material housing | POM | |
| Housing colour | Black | |
| Material electrical contact | Copper alloy | |
| | Galvanised | |
| Material insulation | PVC | |